

Compact • Light • Low Freightage



Key Features

TONIKA® NET 4CH MPEG4 Real-Time Networking DVR provides multiplex function, user-friendly operation, and the most satisfied price to touch your heart.



Remote control multiple DVRs without glitch



Support CMS



Support Remote Console



Support PDA Viewer with video & audio



Support Pen-drive / External HDD backup



Motion Detection recording



Recording, Playback, and Networking



Auto scan set different switch time for each channel

Product Specifications

- 4 composite video inputs (BNC connector)
- 1 Composite & 1 VGA outputs
- Video compression: MPEG4
- Video Format: NTSC and PAL
- 1 channel audio input / output
- Fanless design to lower down the noise
- Display resolution:
 - 720 x 480 / 720 x 576 (NTSC / PAL)
- Display frame rate:
 - Total 120 / 100 fps (NTSC / PAL)
- Hue / Brightness / contrast / Saturation adjustable
- Recording resolution:
 - Full D1: 720 x 480 / 720 x 576 (NTSC / PAL)
 - CIF: 360 x 240 / 360 x 288 (NTSC / PAL)
- Recording frame rate:
 - Full D1: 60 / 50 fps (NTSC / PAL)
 - CIF: 120 / 100 fps (NTSC / PAL)
- Recording mode:
 - Schedule recording (00:00~24:00 set by hour)
 - Continuous / Motion / Sensor recording
- Auto recycle recording
- Auto record enabling
- Remote upgrade system
- Remote access:
 - Support CMS
 - Support PDA Viewer (with video & audio)
 - Support Remote Console & Web Viewer
- Password authentication mechanism
- Playback Mode:
 - Video search by date / time / event
 - 4096 event lists for easy search
 - A-B video repeat playback
- Free Playback Application Software:
 - Playback from Pen drive / External HDD
 - Playback and backup on any PC with Windows 2000 / XP
 - Converting files to AVI format enabling to playback on Windows Media Player
 - Video Enhancer to enhance highest-level video quality
 - Video segment selectable for repeating playback and backup
 - Enabling quick HDD to HDD backup
 - Watermark function for image verification
- I/O
 - 4 Sensor inputs
 - 1 Relay output controlling alarm, lock, light, or other devices
- Operating Temperature: 0°~55°C
- Dimension: (L) 290mm x (M) 180mm x (H) 52mm

Specification Highlight

Item	EB1304 NET
Video input	4
VGA output	1
TV output	1
Audio input/output	1
Sensor input	4
Relay output	1
Display Rate (NTSC / PAL)	120 / 100 fps
Recording Rate (NTSC / PAL)	120 / 100fps
USB Port	1

Application Diagram

